



**PRO
WASH**
Made in America

PWGE/DE Series

Engine Driven Portable Oil Heated



- Gas/diesel engine heavy-duty skid mount units can go where needed without any worries about electrical supply
- Automatic ignition
- Heavy steel construction, oil bath pumps with ceramic plungers, steel pipe coils and stainless steel reservoir for quality and durability
- Ideal for mobile washers, farmers, hog and poultry producers, construction and oil field/s

These durable gas and diesel driven units are completely self-contained—just add water.

PWGE/DE Series

MODEL	PW325HGE ^o	PW30LDE	PW435HGE ^o	PW440VGE ^o	PW440VGE ^G	PW440VGE ^{SF} ^o	PW440HGE ^o	PW530VGE ^o	PW530VGE ^G	PW535HGE ^o	PW535HGE ^G
CAPACITY*	3 GPM	3.5 GPM	4 GPM	4 GPM	4 GPM	4 GPM	4 GPM	5 GPM	5 GPM	5 GPM	5 GPM
PRESSURE*	2500 PSI	3000 PSI	3500 PSI	4000 PSI	4000 PSI	4000 PSI	4000 PSI	3000 PSI	3000 PSI	3500 PSI	3500 PSI
PUMP	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers
ENGINE**	9 HP, Honda, Recoil, Belt Drive	10 HP, Lombardini, Electric Start, Belt Drive	13 HP, Honda, Electric Start, Belt Drive	16 HP, Vanguard, Electric Start, Belt Drive	16 HP, Vanguard, Electric Start, Belt Drive	16 HP, Vanguard, Electric Start, Belt Drive	20 HP, Honda, Electric Start, Belt Drive	16 HP, Vanguard, Electric Start, Belt Drive	16 HP, Vanguard, Electric Start, Belt Drive	20 HP, Honda, Electric Start, Belt Drive	20 HP, Honda, Electric Start, Belt Drive
COIL*** (STEEL PIPE)	95", 1/2" ID, Schedule 80	95", 1/2" ID, Schedule 80	95", 1/2" ID, Schedule 80	126", 1/2" ID, Schedule 80	126", 1/2" ID, Schedule 80	95", 1/2" ID, Schedule 80	126", 1/2" ID, Schedule 80	126", 1/2" ID, Schedule 80	126", 1/2" ID, Schedule 80	126", 1/2" ID, Schedule 80	126", 1/2" ID, Schedule 80
BURNER, PRESSURE ATOMIZING, AUTO IGNITION	Kero, #1 Diesel 230,000 BTU, 12 Volt	Kero, #1 Diesel 230,000 BTU, 12 Volt	Kero, #1 Diesel 230,000 BTU, 12 Volt	Kero, #1 Diesel 350,000 BTU, 12 Volt	Kero, #1 Diesel 350,000 BTU, 115 Volt	Kero, #1 Diesel 230,000 BTU, 12 Volt	Kero, #1 Diesel 350,000 BTU, 12 Volt	Kero, #1 Diesel 350,000 BTU, 12 Volt	Kero, #1 Diesel 350,000 BTU, 115 Volt	Kero, #1 Diesel 350,000 BTU, 12 Volt	Kero, #1 Diesel 350,000 BTU, 110 Volt
GENERATOR	N/A	N/A	N/A	N/A	115 Volt 3000 Watt	N/A	N/A	N/A	115 Volt 3000 Watt	N/A	115 Volt 3000 Watt
FUEL CONSUMPTION	1.66 GPH	1.66 GPH	1.66 GPH	2.5 GPH	2.5 GPH	1.66 GPH	2.5 GPH	2.5 GPH	2.5 GPH	2.5 GPH	2.5 GPH
TANK CAPACITY	Fuel 11 Gal. Gas 1.46 Gal.	Fuel 11 Gal.	Fuel 11 Gal. Gas 1.7 Gal.	Fuel 9.5 Gal. Gas 6 Gal.	Fuel 9.5 Gal. Gas 6 Gal.	Fuel 11 Gal. Gas 2.7 Gal.	Fuel 9.5 Gal. Gas 6 Gal.	Fuel 9.5 Gal. Gas 6 Gal.	Fuel 9.5 Gal. Gas 6 Gal.	Fuel 9.5 Gal. Gas 6 Gal.	Fuel 9.5 Gal. Gas 6 Gal.
TEMP. RISE	110 Degrees	90 Degrees	90 Degrees	125 Degrees	125 Degrees	90 Degrees	125 Degrees	105 Degrees	105 Degrees	110 Degrees	110 Degrees
CHEMICAL	Precise Metered	Low Pressure, Metered	Precise Metered	Precise Metered	Precise Metered	Low Pressure Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered
FLOAT TANK	N/A	N/A	N/A	Stainless Steel	Stainless Steel	N/A	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
TEMPERATURE CONTROL	N/A	Standard	N/A	Optional	Optional	N/A	Optional	Optional	Optional	Optional	Optional
DIMENSIONS	L-40" H-32" W-24"	L-40" H-42" W-24"	L-40" H-42" W-24"	L-48" H-38 1/2" W-34"	L-48" H-38 1/2" W-34"	L-40" H-38 1/2" W-24"	L-48" H-38 1/2" W-34"	L-48" H-38 1/2" W-34"	L-48" H-38 1/2" W-34"	L-48" H-38 1/2" W-34"	L-48" H-38 1/2" W-34"
WEIGHT	530 lbs.	560 lbs.	575 lbs.	705 lbs.	860 lbs.	560 lbs.	870 lbs.	860 lbs.	895 lbs.	875 lbs.	975 lbs.

MODEL	PW325LDE ^o	PW540KGE ^G	PW540LDE ^o	PW550VGE ^G	PW550KGE ^G	PW550LDE ^o	PW830KGE ^G	PW830LDE ^o	PW1025KGE ^G	PW1025HGE ^G	PW1030VGE ^G	PW1030LDE ^G
CAPACITY*	5 GPM	4.5 GPM	4 GPM	4.5 GPM	4.8 GPM	5 GPM	8 GPM	8 GPM	10 GPM	10 GPM	10 GPM	10 GPM
PRESSURE*	3500 PSI	4000 PSI	4000 PSI	5000 PSI	5000 PSI	5000 PSI	3000 PSI	3000 PSI	2500 PSI	2500 PSI	3000 PSI	3000 PSI
PUMP	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers	Triplex, oil bath, ceramic plungers
ENGINE**	23 HP, Lombardini Electric Start, Belt Drive	20 HP, Kohler Command, Belt Drive	20 HP, Lombardi, Electric Start, Belt Drive	23 HP, Vanguard, Electric Start, Belt Drive	25 HP, Kohler, Overhead Valve, Oil Alert, Belt Drive	23 HP, Lombardini Electric Start, Belt Drive	25 HP, Kohler, Overhead Valve, Oil Alert, Belt Drive	23 HP, Lombardini, Electric Start, Belt Drive	25 HP, Kohler, Overhead Valve, Electric Start, Belt Drive	24 HP, Honda, Overhead Valve, Electric Start, Belt Drive	35 HP, B&S Vanguard, Overhead Valve, Electric Start, Belt Drive	26 HP, Lombardini, Electric Start, Belt Drive
COIL*** (STEEL PIPE)	158", 1/2" ID, Schedule 80	158", 1/2" ID, Schedule 80	158", 1/2" ID, Schedule 80	126", .45" ID, Schedule 160	158", .45" ID, Schedule 160	158", 1/2" ID, Schedule 160	158", 1/2" ID, Schedule 80	158", 1/2" ID, Schedule 80	483", 3/4" ID, Schedule 80	483", 3/4" ID, Schedule 80	483", 3/4" ID, Schedule 80	483", 3/4" ID, Schedule 80
BURNER, PRESSURE ATOMIZING, AUTO IGNITION	Kero, #1 Diesel 560,000 BTU, 115 Volt	Kero, #1 Diesel 560,000 BTU, 115 Volt	Kero, #1 Diesel 560,000 BTU, 115 Volt	Kero, #1 Diesel 350,000 BTU, 12 Volt	Kero, #1 Diesel 560,000 BTU, 115 Volt, 1 PH	Kero, #1 Diesel 560,000 BTU, 115 Volt	Kero, #1 Diesel 560,000 BTU, 115 Volt	Kero, #1 Diesel 560,000 BTU, 115 Volt	Kero, #1 Diesel 765,000 BTU, 115 Volt	Kero, #1 Diesel 765,000 BTU, 115 Volt	Kero, #1 Diesel 765,000 BTU, 115 Volt	Kero, #1 Diesel 765,000 BTU, 115 Volt
GENERATOR	115 Volt, 2000 Watt	115 Volt, 3000 Watt	110 Volt, 2000 Watt	NA	115 Volt, 3000 WATT	115 Volt, 2000 WATT	115 Volt, 3000 WATT	115 Volt, 2000 WATT	110 Volt, 3000 WATT	110 Volt, 3000 WATT	110 Volt, 3000 WATT	110 Volt, 2 000 WATT
FUEL CONSUMPTION	4.0 GPH	4.0 GPH	4.0 GPH	2.5 GPH	4.0 GPH	4.0 GPH	4.0 GPH	4.0 GPH	5.5 GPH	5.5 GPH	5.5 GPH	5.5 GPH
TANK CAPACITY	Fuel 27 Gal.	Fuel 12 Gal. Gas 6 Gal.	Fuel 27 Gal.	Fuel 9.5 Gal. Gas 6 Gal.	Fuel 16.75 Gal. Gas 10.5 Gal.	Fuel 27 Gal.	Fuel 16.75 Gal. Gas 10.5 Gal.	Fuel 27 Gal.	Fuel 50 Gal. (Steel) Gas 9 Gal. (Plastic)	Fuel 50 Gal. (Steel) Gas 9 Gal. (Plastic)	Fuel 50 Gal. (Steel) Gas 9 Gal. (Plastic)	Fuel 50 Gal. (Steel)
TEMP. RISE	140 Degrees	140 Degrees	140 Degrees	140 Degrees	140 Degrees	140 Degrees	100 Degrees	100 Degrees	125 Degrees	125 Degrees	125 Degrees	125 Degrees
CHEMICAL	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered
FLOAT TANK	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
TEMPERATURE CONTROL	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
DIMENSIONS	L-54" H-46" W-54"	L-54" H-46" W-54"	L-54" H-46" W-54"	L-48" H-38 1/2" W-34"	L-54" H-46" W-54"	L-54" H-46" W-54"	L-54" H-46" W-54"	L-54" H-46" W-54"	L-72" H-70" W-48"	L-72" H-70" W-48"	L-72" H-70" W-48"	L-72" H-70" W-48"
WEIGHT	1100 lbs.	960 lbs.	1260 lbs.	850 lbs.	1058 lbs.	1260 lbs.	1190 lbs.	1190 lbs.	2075 lbs.	2075 lbs.	2100 lbs.	2100 lbs.



Professional Wash Systems
 3664 Hwy 67N
 Poplar Bluff, Mo 63901
 877-785-3808 Fax: 573-785-1196
 email:professionalwash@semo.net
 web:www.professionalwash.net

*Gallonages and pressure may vary ±5% due to manufacturing tolerances in components.

**Batteries not included.

***ASTM A-53 steel pipe, spiral wound, cold water wrap design, removable. Wheel kits are optional. Note: All 12 volt burner units available with optional high limit control.

o These models available ETL approved to UL1776 and CSA B140.11-M89 specifications. Specifications subject to change without notice.

